



Bottlelight

the charming table lamp

extra bright - and in two steps dimmable

- fits in all standard wine bottles and other bottles with an inner bottleneck diameter of 17-20 mm,
- battery powered and easy to use and installable,
- extra bright and dimmable in two light intensity steps 15 / 40 lm,
- with white light (BOT04-k) or warm-white light (BOT04-w) available,
- works with three standard AA batteries alkaline (1,5V) or rechargeable NiMH batteries,
- illumination time per battery set: 120 hours @ 15 lm, or 40 hours @ 40 lm,
- 100 000 hours lifetime,
- waterproof up to the lid and rain proof from the top,
- no fire danger, no spilling wax,
- ideal for home, restaurants, bars, garden-partys, camping.



BOT04_product information_2021 06 16_EN



Description

The Bottlelight lamp fits into all empty wine, champagne or other bottles with an inner bottleneck diameter of 17-20 mm, and it gives a nice comfortable not dazzling light over a wide surface. Power is supplied by three standard AA alkaline or rechargeable NiMH batteries. The batteries can be easily filled or replaced through the opening with an open lid. For a continuous operation a battery replacement module BOT06 is available.

The Bottlelight can be turned on/off with a first light intensity by turning the lid clockwise/anti-clockwise. Turning the lid further clockwise causes a second brighter intensity, and vice versa. The light intensity can be adjusted comfortably and simply.

The Bottlelight is water resistant against rain from the top. But even as the device is water resistant, it must not be put into beverages. The manufacturer does not accept any liability in such cases.

The device must be kept away from children under the age of 3, because of the batteries.

Our battery supplied "bottlelight" lamp models

Type/Model	Description	EAN/UPS Code
BOT03-k	LED Bottlelight lamp, cold white LED light, 15 lm	0700621847410
BOT03-w	LED Bottlelight lamp, warm-white LED light, 14 lm	0610098499909
BOT03-kT	LED Bottlelight lamp triple pack cold white LED light, 15 lm	0610098499916
BOT03-wT	LED Bottlelight lamp triple pack warm-white LED light, 14 lm	0610098499923
BOT04-w	LED Bottlelight lamp, extra bright, warm white LED light, 15/40 lm adjustable	4893263135055
BOT04-k	LED Bottlelight lamp, extra bright, cold white LED light, 15/40 lm adjustable	0762743431045
BOT05/viviLED®	LED Bottlelight lamp, LED light color and brightness adjustable 10-50 lm	0610098499930
BOT-06	Battery replacement module (for use with USB power adapter)	4893263135062
BOT07	LED Bottlelight lamp, USB rechargeable, touch sensor, very bright 10 - 230 lm	0762743431052

Remark: All BOT03-BOT05 lamps come without batteries, batteries can be ordered separately.

Packaging - Carton Tube (see on the right)

The product comes in a rectangular carton box with pictures, feature descriptions and EAN code printed on it.

Feature description in languages: DE, EN, F, ES, NL, IT.

Size HWD 290 x 75 x 27 mm (11.4 x 2.95 x 1.06 inch);

Total weight inclusive product (without batteries): 105g (0.25 lbs).



Languages

The user manual comes in the following languages: DE, EN, NL, ES, PT, F, I, RU.

Producer and Customs Code

Bottlelight Company Dr. Kitzemaier, Potsdam/Germany, Country of origin: Germany.

Technical Data - BOT04

Length total	256-266 mm ±5mm (10.23-10.63 inch)	LED efficiency	170 lm/W
Length of Light beam	100 mm ±5mm (3.9 inch)	LED light color BOT04-w	warm white, 3000 K
Length within a bottle	230 mm ±5mm (9.1 inch)	LED light color BOT04-k	warm white, 5000 K
International custom ID	8513 1000	Lifetime	100 000 hours
Diameter lower part	17 mm ±0,2mm (0.67 inch)	brightness low intensity	15 lm (adjustable by turning the lid)
Diameter Lid	20 mm ±0,2mm (0.79 inch)	brightness high intensity	40 lm (adjustable by turning the lid)
Materials	Aluminum, acrylic glass, NBR	Supply voltage	2,9 – 5.5 VDC
Weight wt/w batteries	57 ±3g (0.125 lbs) / 126 ±3g (0.278 lbs)	Current consumption	~30mA @ 15lm / ~80mA @ 40lm
Brightness control and off	Switching by slightly turning the lid	Power Supply	3x standard AA cells à 1.5V, or 3x rechargeable NiMH AA cells à 1,2V, or BOT06 battery replacement module (USB)
Operating temperature	-20 ...+65°C (-4 ... 149°F)		
Conformity	CE, RoHS, WEEE-DE 17359610		
Guarantee	3 years		